



Intervid Camera Series
Digital Video Surveillance
with
IP and Analog Cameras



IP-DND-6000

Hybrid IP based and analog, high resolution (480tvl), day/night, high speed PTZ dome with 18x optical zoom lens. This network ready camera utilizes MPEG4 compression and provides D1 resolution.



IP-DNC-5400

Hybrid IP based and analog, high resolution (540tvl), day/night, fixed camera. This network ready camera utilizes MPEG4 compression and provides D1 resolution.



IP-MPD-5500

Hybrid IP based and analog, high resolution (480tvl), color, compact PTZ minidome with 10x optical zoom lens in vandal resistant housing. This network ready camera utilizes MPEG4 compression and provides D1 resolution.



IP-MDC-5400

Hybrid IP based and analog, high resolution (540tvl), day/night, fixed minidome with 4-9mm varifocal auto-iris lens in vandal resistant housing. This network ready camera utilizes MPEG4 compression and provides D1 resolution.



Features	IP-DND-6000	IP-DNC-5400	IP-MPD-5500	IP-MDC-5400
Camera Class	Hybrid (IP and Analog) Day/Night PTZ Dome	Hybrid (IP and Analog) Day/Night Fixed Camera	Hybrid (IP and Analog) Color PTZ MiniDome	Hybrid (IP and Analog) Day/Night Fixed MiniDome
Image Sensor	Sony 1/4" Super HAD CCD	Sony 1/3" Super HAD CCD	Sony 1/4" Super HAD Color CCD	Sony 1/3" Super HAD CCD
Analog Resolution	480tvl	540tvl	480tvl	540tvl
Digital Resolution	D1 (720 x 480)	D1 (720 x 480)	D1 (720 x 480)	D1 (720 x 480)
Minimum Illumination	.7 lux (Color), .05 lux (B&W)	.3 lux (Color), .002 lux (CSU)	1.5 lux	.3 lux (Color), .002 lux (CSU)
Compression Format	MPEG4	MPEG4	MPEG4	MPEG4
Lens	18x Optical Zoom	Provided Separately	10x Optical Zoom	4-9mm Varifocal Auto-Iris
Camera Housing	Provided Separately	Provided Separately	Vandal Resistant	Vandal Resistant

DND-6200-UT



Unitized high resolution (480tvl),

day/night, high speed PTZ dome with 26x optical zoom lens and many other high end features including programmable presets, tours, patterns and privacy zones.

DND-6300



High resolution (540tvl), day/night, high speed PTZ dome with 36x optical zoom lens and many other high end features including programmable presets, tours, patterns and privacy zones.

MPD-6500/MDZ-6500

High resolution (480tvl), day/night, compact PTZ minidome with 22x optical zoom lens in vandal resistant housing. This minidome is also available in a 22x optical zoom



only version where pan/tilt functionality is not required.

MDC-5400



High resolution (540tvl), day/night, fixed minidome with 4-9mm

varifocal auto-iris lens in vandal resistant housing. This minidome is also available with optional LED infrared illuminators for additional lowlight functionality.

MDC-4400



High resolution (540tvl), day/night, fixed minidome with 4-9mm varifocal auto-iris lens in indoor plastic housing.

Features	DND-6200-UT	DND-6300	MPD-6500/MZD-6500	MDC-5400	MDC-4400
Camera Class	Unitized Day/Night PTZ Dome	Day/Night PTZ Dome	Day/Night PTZ MiniDome or Zoom Only Version	Day/Night Fixed MiniDome	Day/Night Fixed MiniDome
Image Sensor	Sony 1/4" Ex-View CCD	Sony 1/4" Ex-View CCD	Sony 1/4" Super HAD CCD	Sony 1/3" Super HAD CCD	Sony 1/3" Super HAD CCD
Analog Resolution	480tvl	540tvl	480tvl	540tvl	540tvl
Wide Dynamic Range	No	Yes	Yes	No	No
Minimum Illumination	1 lux (Color), .01 lux (B&W)	1.4 lux (Color), .01 lux (B&W)	.5 lux (Color), .05 lux (B&W)	.5 lux (Color), .04 lux (B&W)	.5 lux (Color), .04 lux (B&W)
Infrared Illumination	No	No	No	Optional (60' Range)	No
Lens	26x Optical Zoom	36x Optical Zoom	22x Optical Zoom	4-9mm Varifocal Auto-Iris	4-9mm Varifocal Auto-Iris
Camera Housing	Unitized Weather Resistant	Provided Separately	Vandal Resistant	Vandal Resistant	Interior Only (Plastic)

FCZ-5900-UT

Unitized high resolution (480tvl), day/night, zoom camera with 22x optical zoom lens and wide dynamic range.



FCZ-6900

High resolution (480tvl), day/night, zoom camera with 35x optical zoom lens and wide dynamic range.



DNC-5400

High resolution (540tvl), day/night, fixed camera with wide dynamic range.



PVM-201CM

Network ready 20.1" LCD flat panel public view monitor with integrated high resolution (540tvl), day/night, fixed camera with 4-9mm varifocal auto-iris and 40GB hard drive.



PVM-321CM

Network ready 32" LCD flat panel public view monitor with integrated high resolution (540tvl), day/night, fixed camera with 4-9mm varifocal auto-iris and 40GB hard drive.



Features	FCZ-5900-UT	FCZ-6900	DNC-5400	PVM-201CM	PVM-321CM
Camera Class	Unitized Day/Night Zoom Camera	Day/Night Zoom Camera	Day/Night Fixed Camera	Public View Monitor with Integrated Camera	Public View Monitor with Integrated Camera
Image Sensor	Sony 1/4" Super HAD CCD	Sony 1/4" Ex-View CCD	Sony 1/3" Super HAD CCD	Sony 1/3" Super HAD CCD	Sony 1/3" Super HAD CCD
Analog Resolution	480tvl	480tvl	540tvl	540tvl	540tvl
Wide Dynamic Range	Yes	Yes	Yes	No	No
Minimum Illumination	.5 lux (Color), .05 lux (B&W)	.5 lux (Color), .05 lux (B&W)	.5 lux (Color), .002 lux (CSU)	.5 lux (Color), .04 lux (B&W)	.5 lux (Color), .04 lux (B&W)
Infrared Illumination	No	No	No	No	No
Lens	22x Optical Zoom	35x Optical Zoom	Provided Separately	4-9mm Varifocal Auto-Iris	4-9mm Varifocal Auto-Iris
Camera Housing	Unitized Weather Resistant	Provided Separately	Provided Separately	20.1" Public View Monitor	32" Public View Monitor

All specifications are subject to change without notice.



Intervid, Inc.
4650 Wedgewood Boulevard
Suite 102
Frederick, MD 21703
(800) 337-8066
www.intervid.com